QUAD

ALUMINIUM BIFOLD DOOR

Aluminium Bifold Door System

TECHNICAL DATA SHEET

*Image for indicative purposes only

Typical Sizes (standard)	
Max door leaf width	1200mm
Max door leaf height	3000mm
Max weight per door leaf	120KG
Average U-Values	
Double Glazed Center Pane U-Value 1.0	1.5 W/m2K
Triple Glazed Center Pane U-Value 0.6	1.2 W/m2K
Glazing	
Glass Thickness	up to 45mm
Testing	
Energy Rating	B
Security	PAS24 Compliant
Specification options	
Visable Sightline Frame/ Sash	73mm
Track Options	Standard / Low / Integrated Cill
Cills	None / 90mm / 150mm /180mm / 230mm
Clip in bead	✓
Air Permeability	600PA
Water Tightness	600PA
Wind Load Resistance	1800PA
Trickle vents option	✓

Results may vary based on specification. Further details available upon request

Scope

The Aluminium Bi-fold Door system has been designed to meet current and future building regulations, in addition to market-leading features such as our super-slim sightlines. Compliant to PAS24 certification, the door has u-values of just 1.2 W/(m2k) when combined with highly energy efficient glass.

Finishes

- Available in 5 colour ways with the option of bespoke RAL colour to personalise the project.
- Engineering-grade hardware allows for silky smooth opening and closing operation, without the premium price.
- Require very little maintenance to ensure optimal performance and a fresh appearance
- Our aluminium sashes are available in square profile which offers a classic look.

Construction

This aluminium door is constructed using the high-quality bi-fold door profile from Cortizo, fitted with double or triple glazed units.

01782 340111 sales@quadgroup.co.uk quadgroup.co.uk

QUAD Group Ltd, Ravensthorpe Industrial Estate, Low Mill Lane, Havelock St, Ravensthorpe, Dewsbury, WF13 3LN

Due to a policy of continual product development, QUAD Group Ltd reserve the right to alter any of the specifications given in this publication without prior notice. The specification for any given application must be checked with QUAD Group prior to manufacture. No responsibility for accuracy is accepted by QUAD Group. Always refer to the technical manual.